

Automatic flush bolt OLDA 34 HZA-DS type 1



Function:

Automatic, single action flush bolt for non spring-loaded bolting of passive door leaf in double doors.

Features:

OLDA 34 HZA-DS is bolted and unbolted automatically, has bolt Ø 8 x 50 mm, backset 12 mm and forend width 18 mm.

The bolt makes it suitable for integration with automatic drop seals, when there is a large gap between the door leaf and frame or sill and when a sill is not fitted.

Similar dimensions as manual flush bolt OLDA 36 HZM-DS.

Usage:

Recessed into door of wood, steel or aluminium profiles, lower left and upper right, at the edge of passive door leaves, also rebated.

Installation:

Fitted recessed at the edge of the door, either flush with cut-out or without forend cut-out. Fixed with four countersunk 3.5 x 40 mm screws.

Accessories:

Guide tube GT 8 (12) and lock tube LT 8 (13x9) are possible to use.

Strike plates SP 10 and SP 20 are also available.

Specification:

- Automatic, single action and non spring-loaded bolt function
- Bolt:

length: 50 mmdiameter: 8 mmprojection: 15 mm

- o adjustability: -3/+11 mm
- Round electrozinc plated steel forend
- Product:

o width: 18 mm

o height: 189 + 50 mm

o depth: 23 mm

o forend thickness: 3 mm

• Backset including forend: 12 mm

Material: steel

Coating: electrozinc plating

Related products:

- Automatic flush bolts
 - **34 HZA-DS**
 - 43 HZA-20T / -32T 30/60 mm
 - o 33 HZA-R32F Ø 8, 10 & 12 mm
- Manual flush bolts
 - o 34 HZM-DS
 - 33 HZM-20 / -32 30/60 mm
 - o 33 HZM-R32 Ø 8, 10 & 12 mm

Service:

Function & system tests are recommended once or twice a year. Test, lubricate and adjust moving parts as needed.


In harsh environments or high frequent use, tests should be made more often.


Warranty:

All mechanical "OLDA" branded products have a 36-month factory warranty.



Automatic flush bolt OLDA 34 HZA-DS type 1





Product documents:

- Dimensions
- Installation with forend cut-out
- Installation without forend cut-out

Product views – 2D:

- PDF
- DXF
- DWG

Product models - 3D:

- STEP
- DWG
- PDF 3D

OLDA product links:

- Automatic flush bolt 34 HZA-DS
- Manual flush bolt 36 HZM-DS
- Flush bolt accessories
- OLDA flush bolt guide
- OLDA fittings school